



Tel: +4 0722 279 481
+4 0725 984 004

Email: comercialgritsablare@gmail.com
Web: www.gritsablare.ro

Solutii Economice de Sablare & Curatare

Linie Dedicata pentru Echipamente Profesionale de Sablare

Airless Spray Pump 63:1 Parts by GritSablare

Section 1. Accessories



GUN FILTER

Mesh: 30, 50, 65, 100, 150, 200
Mesh: 60, 100



SURGE FILTER

Mesh: 30, 50, 60, 100, 150, 200, 300



GUN TIP FILTER

Mesh: 30, 60, 80, 100, 150, 200



PAINT AGITATOR

Recommended speed: 300 - 3000 rpm



SWIVEL (GUN, HOSE, Z-SWIVEL)

Size: 1/4", 3/8", 1/2", 1/4" x 3/8"



PAINT HOSE

Size: 3/16", 1/4", 3/8" (wire & textile)



FLUID FILTER

Big & small (carbon, stainless steel, Aluminium)



SWITCH GUARD (RAC5, RACX) / FLAT TIP GUARD

Size: 7/8", 1 1/16"



SUCTION FILTER (15 Mesh)

Size: 1", 3/4"



SPRAY GUN REPAIR KIT

S-P gun & XTR gun & all gun RPK



REPAIR KIT

68:1 Xtreme & Electric pump (244851, 244194)



TS-OIL

Capacity: 236 ml



BALL VALVE

1/4" x 1/4" (Hammer valve is also available)



ROD & SLEEVE FOR ELECTRIC PUMP



GUN NOZZLE

Size: 7/8"

Section 2. Gun



PRESSURE RATE
500 bar (7,250 psi)

Feature

Stainless steel swivel, needle and sheet
Adhesive, Lubricants, Sealants, Mastics etc



PRESSURE RATE
350 bar (5,000 psi)

Feature

Four finger and two finger trigger are available.
FORGED ALUMINUM



PRESSURE RATE
250 bar (3,600 psi)

Feature

Light weight type
Four finger and two finger trigger are available



PRESSURE RATE
510 bar (7,396 psi)

Feature

Suitable for high viscosity material industrial spraying job, texture paint spraying.



PRESSURE RATE
700 bar (10,000 psi)

Feature

Steel Plated Fluid Passage
Tungsten Carbide Ball Durability



IN SPRAY COATING PIPELINE
HOLE SCOPE (MM)
Ø 300-1200 (12-47")

Feature

Fuselage length (mm) : 950
Fuselage weight (kg) : 18



PRESSURE RATE
350 bar (5,000 psi)

Feature

Leather packings for a long life time. Sizes (2feet, 3feet, 3feet, 4feet, 6feet, 8feet)



PRESSURE RATE
350 bar (5,000 psi)

Feature

Easy trigger pulling for precise material dispense. Tungsten carbide ball and seat assure wear resistance



PRESSURE RATE
250 bar (3,600 psi)

Feature

Applied to zinc material fabricated heavy materials

Section 3. Regulators



FLUID PRESSURE - 3 type: 34-140bar / 34-220bar / 100-340bar

Feature

Control and regulate fluid pressure to one spray gun dispensing valve or atomizing head in airless spray system



FLUID PRESSURE - 2 type: 0-70bar / 70-207bar

Feature

Regulator back pressure to gun and maintain proper pressure. For circulation in high pressure spray circulation system



FLUID PRESSURE - 344bar

Feature

Control downstream pressure for mastic or semi-solid material. Provide precise pressure control to each spray gun



FLUID PRESSURE - 3,600 PSI (250 BAR)

Feature

RELIEF VALVE



FLUID PRESSURE - 14-70bar / 70-207 bar

Feature

Control and regulate fluid pressure to one spray gun dispensing valve or atomizing head in airless spray system



Feature

For accurate control of fluid pressure to one spray gun dispensing valve, or atomizing head. Material: stainless steel



Tel: +4 0722 279 481
+4 0725 984 004

Email: comercialgritsablare@gmail.com
Web: www.gritsablare.ro

Solutii Economice de Sablare & Curatare

Linie Dedicata pentru Echipamente Profesionale de Sablare

Section 4. Product Identification

Product name

Airless Spray Pump 63:1 Parts by GritSablare

Distributor:

GritSablare

Headquarter: 10 Eliza Zamfirescu Leonida Street, Bucharest

Storage & Logistic: Constanța Seaport, Gate 2, SORENA Platform, Constanța, Romania

Phone: (+4) 0722.279.481

Email: comercialgritsablare@gmail.com

Website: www.gritsablare.ro