



GritSablare, official partner of Gläsner in Romania

Pressure Fan: Mobile - Gläsner HL

PRODUCT SPECIFICATIONS

Section I. Company Identification

Product Name	Pressure Fan: Gläsner HL
Manufacturer	Gläsner Sandstrahl Maschinenbau GmbH, Germany
Distributor	GritSablare Official Romanian Partner of Gläsner
Headquarter:	10 Eliza Zamfirescu Leonida Street, Bucharest
Storage & Logistic:	Termele Romane Street (between Gate 1 / Gate 2), Constanța Seaport, Romania
Phone:	(+4) 0722.279.481
Fax:	(+4) 0372.870.589
Email:	comercialgritsablare@gmail.com
Website:	www.gritsablare.ro

Section II. Advantages

HL Standard Model


Variants: 18 / 40 / 60 / 100 / 140 / 200 litre capacity

- Mobile design
- 5 m special sandblasting, hose 25 x 7 mm
- 1 pc. special rapid hose coupling
- 1 pc. nozzle holder with 1¼" thread
- 1 pc. continuous blasting nozzle optionally in 4, 5, 6 or 8 mm Ø
- 1 pc. sandblaster head protection cover model S 6
- 5 m fresh air hose 9 mm c. w.


Section III. Blasting Usage



Metallic




Car Parts



Brick Walls




Agriculture



Fences



Marble



Glass

Section IV. Product Description

- **Fully automatic remote control (dead man's handle) with manual-operated valve and control line, installed, for models of 60, 100, 140 and 200 litres capacity.**
- Suitable for all common blast-media, mobile version, with one axis, two solid rubber wheels and a frame to relocate the system.
- The top side of the pressure pot works as a filling sinkhole
- Automatic filling valve
- Closable inspection plate
- Blast media volume adjustment-unit
- Pipes R 1 ¼"
- Pressured-air stop valve
- Pressured-air entry-coupling
- Air-taking device for protective hood
- Tank coupling R 1 ¼" to connect blast hose.

Section V. Air Consumption

Air consumption of the permanent blast nozzles with a blast pressure of 5 - 6 bar.

Blast Nozzle	Compressed Air Capacity
4,0 mm	900 litres/min.
5,0 mm	1400 litres/min.
6,0 mm	2000 litres/min.
8,0 mm	4000 litres/min.

Section VI. Optional equipment

- Oil- and water separator with attached pressure reducing valve and manometer, installed and ready to use.
- Special sandblast pressure fan hose 25 mm i.W. (5 meters included in basic system) additional hose per meter.
- Finishing in texture paint. Custom-specific painting is available.